

Mail.XML Version 26.0

System Messages Specification

September 19, 2022

Working Group Chair

Shawn Baldwin, WindowBook

Technical Director

Shariq Mirza, DTAC Associate, Assurety Consulting & Solutions

Editor:

Shariq Mirza, DTAC Associate, Assurety Consulting & Solutions

Copyright (c) 2022 – Delivery Technology Advocacy Council (“DTAC”). All Rights Reserved.

Mail.dat is a registered trademark of DTAC

Mail.XML is a trademark of DTAC



Copyright and Legal Notices

© 2022 Delivery Technology Advocacy Council. All Rights Reserved.

Copyright 2022 – Delivery Technology Advocacy Council (“DTAC”) is the “Copyright Owner” of “Mail.XML®”. All rights reserved by the Copyright Owner under the laws of the United States, Belgium, the European Economic Community, and all states, domestic and foreign. This document may be downloaded and copied provided that all copies retain and display the copyright and any other proprietary notices contained in this document. This document may not be sold, modified, edited, or taken out of context such that it creates a false or misleading statement or impression as to the purpose or use of the Mail.XML® specification, which is an open standard. Use of this Standard, in accord with the foregoing limited permission, shall not create for the user any rights in or to the copyright, which rights are exclusively reserved to the Copyright Owner.

DTAC and the members of the Mail.XML® Specifications - Committee (collectively and individually, "Presenters") make no representations or warranties, express or implied, including, but not limited to, warranties of merchantability, fitness for a particular purpose, title, or non-infringement. The presenters do not make any representation or warranty that the contents of this document are free from error, suitable for any purpose of any user, or that implementation of such contents will not infringe any third party patents, copyrights, trademarks or other rights. By making use of this document, the user assumes all risks and waives all claims against Presenters.

In no event shall Presenters be liable to user (or other person) for direct, indirect, special or consequential damages arising from or related to any use of this document, including, without limitation, lost profits, business interruption, loss of programs, or other data on your information handling system even if Presenters are expressly advised of the possibility of such damages.

Some states do not allow the disclaimer or limitation of damages, so the disclaimers set forth above apply to the maximum extent permitted under applicable law.

Abstract

This document describes the messaging protocol for use by mailers and their consignees. The Mail.XML™ Transaction Protocol defines the roles and responsibilities of Shippers and Consignees and defines the format and method for message exchange. This messaging protocol is designed to be XML and Web-Services compliant.

Mail.XML and Mail.dat are trademarks of DTAC.

About Mail.XML™

Mail.XML™ is bringing a paradigm change to the industry by increasing business function specific B2B (Business to Business) communication within the industry that supports automation and in the end enables cost avoidance and higher profits through improved competence and effectiveness of communication. Mail.XML is designed to increase efficiency and lower costs by removing many manual data entry processes and enabling quick near real time communication between business partners. Mail.XML currently supports container based scheduling, pick up and drop off business processes, as well as identifying different business entities responsible for performing different services such as quality of mailing, address correction, and delivery confirmation on a mailing. The core focus of Mail.XML is communication between industry members and from industry to the final mail processing and delivery organization that delivers the mail to the end consumer, e.g., USPS. In the next few versions of Mail.XML the focus moves across mailing supply chain channels, and includes advanced functions such as payment; automated verification; enabling first, second, and third party communication and incorporating presort planning, printing, and distribution processes.

What's New in Mail.XML Version 26.0?

With this release, the Mail.XML Messaging Protocol moves to Version 26.0. This release supports structure changes required by mailing industry and Postal Service.

Changes supported by Mail.XML 26.0 include:

- CR 2601 - Align the Mail.XML with Informed Delivery application: Decrease the Campaign Title from 60 to 40 characters, and Increase the Display Name from 30 to 40 characters
- CR 2603 - Added new values, RG and CR, to characteristicIncentiveType to support promotions
- CR 2604 - Added new value, 2, to zoneICType
- CR 2605 - Removed the value associated with the Outside Parcel Processing Category
- CR 2606 - Removed the Rate Type and Rate Category values for Priority Mail Regional Rate Boxes so that this decommissioned product may not be available.
- CR 2607 - Removed the Containerization Discount enumeration values from the rateCategoryType type
- CR 2609 - Added rateLevelType enumerations for missing Container Quantity Detail Rate Levels
- CR 2610 - Removed commercialplus from priceType type
- CR 2611 - Removed "FSS" related enumeration values from various types

About Mail.XML Schema Modularization

Today Mail.XML messages are grouped into 8 message types.

- Transportation Messages (TM)
- Mailing Messages (MM)
- Data Distribution Messages (DD)
- Dynamic Payment Template Messages
- Identification Messages (ID)
- Supply Chain Messages (SC)
- Informed Visibility (IV)
- System Messages
- Base: Shared simple types
- Definitions: Shared complex types and elements

The simple types shared across 2 or more modules are found in the Base schema. Likewise, the shared definitions module contains complex type definitions and elements that are shared across 2 or more modules.

Mail.XML Module Versioning Rules

The following versioning rules will be followed:

The Mail.XML wrapper schema**(.xsd) will always be given the next higher version number (or Errata designation) when any update is made to base, defs or any module. The name of the .xsd file will indicate the new version and the new version number will be used in the namespace and target declarations: `xmlns:mailxml="http://delivery-tech.org/Specs/mailxml26.0/mailxml"`
`targetNamespace="http://delivery-tech.org/Specs/mailxml26.0/mailxml"`

- When updates are made, only those modules that are updated will be given the next higher version number (or Errata letter designation).
- If updates are made to the base or defs, then the base and defs xsds will be given the next higher version number (or Errata designation) and all modules that call to them will also be given the next higher version number (or Errata designation).

For example:

- If the wrapper version is labeled as xmlns:mailxml="http://delivery-tech.org/Specs/mailxml26.0A/mailxml" then at least one of the XSDs is at same version such as filename ='Mail.XML_26.0A.xsd' <- Errata A
- If the wrapper version is labeled as xmlns:mailxml="http://delivery-tech.org/Specs/mailxml26.0B/mailxml" then at least one of the XSDs is at same version such as filename ='Mail.XML_26.0B.xsd' <- Errata B
- If the wrapper version is labeled as xmlns:mailxml="http://delivery-tech.org/Specs/mailxml26.0/mailxml" then at least one of the XSDs is at same version such as filename ='Mail.XML_26.0.xsd' <- Major Version

Mail.XML 26.0 XSD Modules:

The following Mail.XML XSD modules/namespaces are used:

- Mail.XML_tm.xsd: This module contains all the transportation (or FAST) messages and the attributes, elements and complex types that are unique to these messages. Namespace=Mail.XML_tm:
- Mail.XML_mm.xsd: This module contains all the mailing messages (eDoc) and the attributes, elements and complex types that are unique to these messages. Namespace=Mail.XML_mm:
- Mail.XML_iv.xsd: This module contains informed visibility messages and the attributes, elements and complex types that are unique to these messages. Namespace=Mail.XML_iv:
- Mail.XML_dd.xsd: This module contains all the data distribution messages and the attributes, elements and complex types that are unique to these messages. Namespace=Mail.XML_dd:
- Mail.XML_id.xsd: This module contains all the identification messages and the attributes, elements and complex types that are unique to these messages. Namespace=Mail.XML_id:
- Mail.XML_sc.xsd: This module contains all the supply chain messages and the attributes, elements and complex types that are unique to these messages. Namespace=Mail.XML_sc:
- Mail.XML_defs.xsd: This module contains all the common definitions of attributes, elements and complex types that are used across two or more message types. Namespace=Mail.XML_defs:
- Mail.XML_base.xsd: This module contains simple types that are shared across two or more modules that make up Mail.XML. These can be considered a building block for any message group. Namespace=Mail.XML_base:
- Mail.XML.xsd: This module contains the system messages of Mail.XML and is used to build custom profiles for Mail.XML. Namespace=Mail.XML:

The Mail.XML™ 26.0 Messaging Documentation Set

The Mail.XML Messaging Specification has been organized into a set of documents. This *Schemas Specification* is one document in a set of documents that make up the Mail.XML Specification 26.0. Updates in this Specification are NOT backwardly compatible with previous versions. Other documents in the specification set include:

- Mail.XML™ 26.0: Transportation Messaging Specification documents all transportation messages
- Mail.XML™ 26.0: Mailing Messaging Specification documents all mailing messages
- Mail.XML™ 26.0: Informed Visibility Specification documents all informed visibility messages
- Mail.XML™ 26.0: Data Distribution Messaging Specification documents all data distribution messages
- Mail.XML™ 26.0: Identification Messaging Specification documents all identification messages
- Mail.XML™ 26.0: Supply Chain Messaging Specification documents all supply chain messages
- Mail.XML™ 26.0: System Messaging Specification documents all systems and fault messages
- Mail.XML™ 26.0: Simple Types Specification documents all simple types used across Mail.XML messages
- Mail.XML™ 26.0: Common Definitions Specification documents all shared elements and complex types.
- Mail.XML™ 26.0: Schemas contains the .XSDs that make up the Mail.XML Messaging Specification

Table of Contents

Abstract	3
About Mail.XML™	3
What's New in Mail.XML Version 26.0?	3
About Mail.XML Schema Modularization	4
Mail.XML Module Versioning Rules	4
The Mail.XML™ 26.0 Messaging Documentation Set	6
Index	8
Elements – Complex Types – Simple Types.....	10

Index

Schema mailxml_tm_26.0.xsd

schema location: [../XSDs/mailxml_tm_26.0.xsd](#)
attribute form default: **qualified**
element form default: **qualified**
targetNamespace: http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm

Elements

[ActualConsigneeFacility](#)

[ActualEndUnload](#)
[ActualStartUnload](#)
[ActualTruckArrival](#)
[AllApptCloseoutDelivery](#)
[AllApptCloseoutNotification](#)
[AllApptCloseoutResponse](#)
[AllDeliveryApptCloseoutRequest](#)
[AllPickupApptCloseoutRequest](#)
[ApptInductionCloseoutRequest](#)
[ApptInductionCloseoutResponse](#)
[ApptStatus](#)
[ConsigneeGoodsReceipt](#)
[ConsigneeGoodsReceiptDelivery](#)
[ConsigneeGoodsReceiptNotification](#)
[CustomerSupplierAgreementQueryRequest](#)
[CustomerSupplierAgreementQueryResponse](#)
[DeliveryApptCancelCreateRequest](#)
[DeliveryApptCancelCreateResponse](#)
[DeliveryApptCancelRequest](#)
[DeliveryApptCancelResponse](#)
[DeliveryApptContentRemoveRequest](#)
[DeliveryApptContentRemoveResponse](#)
[DeliveryApptCreateRequest](#)
[DeliveryApptCreateResponse](#)
[DeliveryApptMultiStopUpdateRequest](#)
[DeliveryApptQueryRequest](#)
[DeliveryApptQueryResponse](#)
[DeliveryApptShellCancelRequest](#)
[DeliveryApptShellCancelResponse](#)
[DeliveryApptShellCreateRequest](#)
[DeliveryApptShellCreateResponse](#)
[DeliveryApptShellUpdateRequest](#)
[DeliveryApptShellUpdateResponse](#)
[DeliveryApptStatusQueryRequest](#)
[DeliveryApptStatusQueryResponse](#)

[DeliveryApptTransportationUpdateRequest](#)
[DeliveryApptTransportationUpdateResponse](#)

Complex types

[actualBedloadType](#)

[actualPalletType](#)
[allDeliveryApptCloseoutAcceptType](#)
[AppointmentInfoType](#)
[apptBlockGoodsType](#)
[apptBlockRequestType](#)
[apptBlockUnscheduledGoodsType](#)
[apptBlockUpdateType](#)
[apptCloseoutDetailType](#)
[apptCloseoutNotAvailableResponseType](#)
[apptCloseoutResponseType](#)
[apptInfoType](#)
[availableApptType](#)
[availableHourType](#)

[availableSlotType](#)

[bedloadHandlingUnitType](#)

[bedloadUnitType](#)

[carrierType](#)

[containerInductionInfoType](#)

[contentCancelType](#)

[contentDetailInfoType](#)

[contentDetailInfoUpdateType](#)

[contentUspsSummaryType](#)
[contentUspsSummaryUpdateType](#)

[csaDispatchType](#)

[csaInfoType](#)

[deliveryApptAcceptType](#)
[deliveryApptContentRemoveAcceptType](#)
[deliveryApptContentRemoveRejectType](#)
[deliveryApptRejectType](#)
[deliveryApptShellAcceptType](#)
[deliveryApptShellCancelRequestType](#)
[deliveryApptShellCancelResponseType](#)
[deliveryApptShellRejectType](#)
[deliveryApptTransportationUpdateRequestType](#)
[deliveryApptTransportationUpdateResponseType](#)

[deliveryApptUpdateAcceptType](#)
[deliveryApptUpdateRejectType](#)

Simple types

[appointmentNumberIdentifierType](#)
[contentsBarcodeStatusType](#)
[contentsBarcodeTypeType](#)
[csaStatusType](#)
[csaTemplateType](#)
[IMcbInfoType](#)
[locationStatusType](#)
[packageServicesType](#)
[processingCodeType](#)
[scanEventType](#)
[stopStatusType](#)
[valueAddedServiceType](#)
[verificationLocationType](#)

<u>DeliveryApptUpdate</u>	<u>deliveryContentAcceptType</u>
<u>DeliveryApptUpdateRequest</u>	<u>deliveryContentCancelRequestType</u>
<u>DeliveryApptUpdateResponse</u>	<u>deliveryContentCancelResponseType</u>
<u>DeliveryContentCancelRequest</u>	<u>deliveryContentRejectType</u>
<u>DeliveryContentCancelResponse</u>	<u>deliveryContentUpdateAcceptType</u>
<u>DeliveryContentCreateRequest</u>	<u>deliveryContentUpdatedType</u>
<u>DeliveryContentCreateResponse</u>	<u>deliveryContentUpdateRejectType</u>
<u>DeliveryContentQueryRequest</u>	<u>deliverySummaryType</u>
<u>DeliveryContentQueryResponse</u>	<u>detailInfoType</u>
<u>DeliveryContentUpdateRequest</u>	<u>eFileSamplingTimeType</u>
<u>DeliveryContentUpdateResponse</u>	<u>maildatSummaryType</u>
<u>DeliveryReApptRequest</u>	<u>oneTimeApptType</u>
<u>DispatchContainerInfoNotification</u>	<u>optionalApptType</u>
<u>DispatchContainerInfoResponse</u>	<u>optReturnInfoType</u>
<u>GoodsReceiptResponse</u>	<u>palletPresortType</u>
<u>OpenApptQueryRequest</u>	<u>palletUnitType</u>
<u>OpenApptQueryResponse</u>	<u>PartnerApptBlockType</u>
<u>PartnerApptQueryRequest</u>	<u>partnerContentAssignmentType</u>
<u>PartnerApptQueryResponse</u>	<u>pickupApptBlockRequestType</u>
<u>PartnerContentAssignmentRequest</u>	<u>presortType</u>
<u>PartnerContentAssignmentResponse</u>	<u>recurringApptBlockType</u>
<u>PickupApptCancelRequest</u>	<u>recurringApptType</u>
<u>PickupApptCancelResponse</u>	<u>slotAvailabilityType</u>
<u>PickupApptCreateRequest</u>	<u>staleContentNotificationElementType</u>
<u>PickupApptCreateResponse</u>	<u>trailerInfoType</u>
<u>PickupApptUpdateRequest</u>	<u>trailerType</u>
<u>PickupApptUpdateResponse</u>	<u>transportationContainerBlockType</u>
<u>RecurringApptQueryRequest</u>	<u>transportationContainerStatusBlockType</u>
<u>RecurringApptQueryResponse</u>	<u>transportationDetailBlockType</u>
<u>ScheduledAppt</u>	<u>transportationGeoDataBlockType</u>
<u>StaleContentDelivery</u>	<u>transportationSummaryBlockType</u>
<u>StaleContentNotification</u>	<u>trayHandlingUnitType</u>
<u>StaleContentQueryRequest</u>	<u>uspsClosedBySVType</u>
<u>StaleContentQueryResponse</u>	<u>uspsContainerInfoType</u>
<u>UnscheduledConsigneeGoodsReceipt</u>	<u>uspsDetailType</u>
<u>UnscheduledConsigneeGoodsReceiptDelivery</u>	<u>uspsSummaryType</u>
<u>UnscheduledConsigneeGoodsReceiptNotification</u>	
<u>USPSDeliveryContentUpdatedDelivery</u>	
<u>USPSDeliveryContentUpdatedNotification</u>	
<u>USPSDeliveryContentUpdatedQueryRequest</u>	
<u>USPSDeliveryContentUpdatedQueryResponse</u>	

Elements – Complex Types – Simple Types

element **ActualConsigneeFacility**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	mailxml_defs:consigneeFacilityType
children	mailxml_defs:CompanyName mailxml_defs:FacilityNumber mailxml_defs:FacilityAddress mailxml_defs:FacilityAddress mailxml_defs:FacilityName mailxml_defs:FacilityType mailxml_defs:URL mailxml_defs:CommonContact
used by	complexTypes apptBlockGoodsType apptBlockUnscheduledGoodsType

element **ActualEndUnload**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	xs:dateTime
used by	complexTypes apptBlockGoodsType apptBlockUnscheduledGoodsType apptInfoType
annotation	documentation Actual date/time when unload is complete

element **ActualStartUnload**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	xs:dateTime
used by	complexTypes apptBlockGoodsType apptBlockUnscheduledGoodsType apptInfoType

element **ActualTruckArrival**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm

type	xs:dateTime
used by	complexTypes apptBlockGoodsType apptBlockUnscheduledGoodsType apptInfoType

element **AllApptCloseoutDelivery**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_defs:DataRecipient mailxml_tm:UserLicenseCode mailxml_tm:MaildatJobID mailxml_tm:CustomerGroupID mailxml_tm:MailingGroupID mailxml_tm:PushMessageID mailxml_tm:FullServiceAllApptCloseoutAccept
annotation	documentation Delivery of full service closeout data of appointments from USPS.

element **AllApptCloseoutNotification**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm

children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:CRID mailxml_tm:PushMessageID mailxml_tm:UserLicenseCode mailxml_tm:MaidatJobID mailxml_tm:CustomerGroupID mailxml_tm:MailingGroupID mailxml_tm:NotificationDate
annotation	documentation Notification from UPSP that full service closeout data is ready to be picked up.

element AllApptCloseoutResponse

diagram	<p>The diagram illustrates the structure of the AllApptCloseoutResponse element. It is a sequence of the following components:</p> <ul style="list-style-type: none"> Attributes: A group of attributes including <code>mailxml_defs:LargeTrans...</code>, <code>mailxml_defs:MessageGroupID</code>, <code>mailxml_defs:TotalMessageCou...</code>, <code>mailxml_defs:MessageSerialNu...</code>, <code>mailxml_defs:TransmittedRecor...</code>, <code>mailxml_defs:TotalRecordsAcro...</code>, and <code>mailxml_defs:LastMessage</code>. Elements: <ul style="list-style-type: none"> <code>mailxml_tm:TrackingID</code> <code>mailxml_tm:SubmitterTrackingID</code> <code>mailxml_defs:LargeTransactio...</code> A choice between two <code>mailxml_tm:AllDeliveryApptClo...</code> elements: <ul style="list-style-type: none"> Response indicating that all delivery appointments have been closed. Response indicating that all delivery appointments could not be closed and why.
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_defs:LargeTransactionDividerResult mailxml_tm:AllDeliveryApptCloseoutAccept mailxml_tm:AllDeliveryApptCloseoutReject
annotation	documentation Response to the request to closeout all delivery appointments.

element **AllDeliveryApptCloseoutRequest**

diagram	<p>The diagram shows the structure of the AllDeliveryApptCloseoutRequest element. It has a main box labeled AllDeliveryApptCloseoutRequest with the description "Request to closeout all delivery appointments." To its right is an attributes container. Inside this container is a group grp mailxml_tm:StatusReques... which contains several attributes: mailxml_tm:SchedulerID, mailxml_tm:SchedulerCRID, mailxml_tm:SchedulerCorpID, mailxml_tm:CreatorSchedulerC..., mailxml_tm:CreatorSchedulerID, mailxml_tm:CreatorSchedulerC..., mailxml_tm:Start, and mailxml_tm:End. Below the attributes container is a connector box (a circle with three dots) that connects to three child elements: mailxml_tm:SubmittingParty, mailxml_tm:SubmittingSoftware, and mailxml_tm:SubmitterTrackingID.</p>
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID
annotation	documentation Request to closeout all delivery appointments.

element **AllPickupApptCloseoutRequest**

diagram	<p>The diagram shows the structure of the AllPickupApptCloseoutRequest element. It has a main box labeled AllPickupApptCloseoutRequest with the description "Message sent from the Shipper to the Consignee to check the closeout status of all pickup appointments--scheduled and unscheduled." To its right is an attributes container. Inside this container are four attributes: mailxml_tm:ShipperID, mailxml_tm:ShipperCorpID, mailxml_tm:Start, and mailxml_tm:End. Below the attributes container is a connector box (a circle with three dots) that connects to three child elements: mailxml_tm:SubmittingParty, mailxml_tm:SubmittingSoftware, and mailxml_tm:SubmitterTrackingID.</p>
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID
annotation	documentation Message sent from the Shipper to the Consignee to check the closeout status of all pickup appointments--scheduled and unscheduled.

element **ApptInductionCloseoutRequest**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:ApptCloseout
annotation	documentation Message sent by the Consignee to the Shipper to request induction closeouts.

element **ApptInductionCloseoutResponse**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:ApptInductionCloseoutAccept mailxml_tm:ApptInductionCloseoutReject
annotation	documentation Response from the Shipper providing induction closeout information.

element **ApptStatus**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	mailxml_base:apptStatusType

used by	complexTypes apptBlockGoodsType apptBlockUnscheduledGoodsType
---------	---

element **ConsigneeGoodsReceipt**

<p>diagram</p>	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ApptBlockGoodsReceipt mailxml_tm:DetailInfo mailxml_tm:TrailerInfo mailxml_tm:ReturnInfo
used by	<p>elements AllApptCloseoutResponse/AllDeliveryApptCloseoutAccept DeliveryApptStatusQueryResponse/QueryResults</p> <p>complexType allDeliveryApptCloseoutAcceptType</p>
annotation	<p>documentation</p> <p>A report or message indicating delivery closeout status for a scheduled appointment.</p>

element ConsigneeGoodsReceiptDelivery

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_defs:DataRecipient mailxml_tm:UserLicenseCode mailxml_tm:MaidatJobID mailxml_tm:CustomerGroupID mailxml_tm:MailingGroupID mailxml_tm:PushMessageID mailxml_tm:ApptBlockGoodsReceipt mailxml_tm:DetailInfo mailxml_tm:TrailerInfo mailxml_tm:ReturnInfo
annotation	documentation Delivery of a consignee goods receipt from the USPS

element ConsigneeGoodsReceiptNotification

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:CRID mailxml_tm:PushMessageID mailxml_tm:UserLicenseCode mailxml_tm:MaidatJobID mailxml_tm:CustomerGroupID mailxml_tm:MailingGroupID mailxml_tm:NotificationDate
annotation	documentation Notification that a consignee goods receipt is ready for pickup from the USPS.

element CustomerSupplierAgreementQueryRequest

diagram	<p>The diagram shows the structure of the CustomerSupplierAgreementQueryRequest element. It has a title box labeled "CustomerSupplierAgreement..." with the description "Query request for for a Customer Supplier Agreement (CSA)". The element contains an attributes group with a grp mailxml_tm:CustomerSup... group. This group contains two attributes: mailxml_tm:OwnerCRID and mailxml_tm:CSAID. Additionally, there is a choice group (indicated by a circle with four dots) containing three elements: mailxml_tm:SubmittingParty, mailxml_tm:SubmittingSoftware, and mailxml_tm:SubmitterTrackingID.</p>
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID
annotation	documentation Query request for for a Customer Supplier Agreement (CSA).

element CustomerSupplierAgreementQueryResponse

diagram	<p>The diagram shows the structure of the CustomerSupplierAgreementQueryResponse element. It has a title box labeled "CustomerSupplierAgreement..." with the description "Response to the Query request for for a Customer Supplier Agreement (CSA)". The element contains an attributes group with a grp mailxml_tm:CustomerSup... group. This group contains two attributes: mailxml_tm:OwnerCRID and mailxml_tm:CSAID. Additionally, there is a choice group (indicated by a circle with four dots) containing three elements: mailxml_tm:TrackingID, mailxml_tm:SubmitterTrackingID, and a nested choice group. The nested choice group (indicated by a circle with a vertical line) contains two elements: mailxml_tm:QueryResults and mailxml_tm:QueryError.</p>
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:QueryResults mailxml_tm:QueryError
annotation	documentation Response to the Query request for for a Customer Supplier Agreement (CSA).

element **DeliveryApptCancelCreateRequest**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:DestinationEntry mailxml_tm:ApptCancel mailxml_tm:ApptBlock mailxml_tm:DetailInfo mailxml_tm:TrailerInfo
annotation	documentation Request to cancel a delivery appointment and create a new one.

element **DeliveryApptCancelCreateResponse**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:ReturnInfo mailxml_tm:ApptCancel

	mailxml_tm:DeliveryApptAccept mailxml_tm:DeliveryApptReject
annotation	documentation Response to the request to cancel a delivery appointment and create a new one.

element **DeliveryApptCancelRequest**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:DestinationEntry mailxml_tm:ReturnInfo
annotation	documentation Request to cancel a delivery appointment.

element **DeliveryApptCancelResponse**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:DeliveryApptCancelAccept mailxml_tm:DeliveryApptCancelReject
annotation	documentation Response to the request to cancel a delivery appointment.

element **DeliveryApptContentRemoveRequest**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:ContentID
annotation	documentation Request to remove content from a delivery appointment.

element **DeliveryApptContentRemoveResponse**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:DeliveryApptContentRemoveAccept mailxml_tm:DeliveryApptContentRemoveReject
annotation	documentation Response to the request to remove content from a delivery appointment.

element DeliveryApptCreateRequest

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:DestinationEntry mailxml_tm:RecurringAppt mailxml_tm:OneTimeAppt mailxml_tm:DetailInfo mailxml_tm:TrailerInfo mailxml_tm:ConsigneeFacility mailxml_tm:Comment mailxml_tm:ValueAddedService
annotation	documentation Request to create a delivery appointment.

element DeliveryApptCreateResponse

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm

children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:DeliveryApptCreateAccept mailxml_tm:DeliveryApptCreateReject
annotation	documentation Response to the request to create a delivery appointment.

element **DeliveryApptMultiStopUpdateRequest**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:ReturnInfo
annotation	documentation Request to update a multistop delivery appointment.

element **DeliveryApptQueryRequest**

diagram	<p>DeliveryApptQueryRequest Query request for for availablity of a particular appointment.</p> <p>attributes</p> <ul style="list-style-type: none"> grp mailxml_defs:RequestMs... <ul style="list-style-type: none"> mailxml_defs:ShipperApptRequ... mailxml_defs:ConsigneeApptID mailxml_defs:SchedulerID mailxml_defs:SchedulerCorplD mailxml_defs:SchedulerCRID mailxml_defs:ShipperMultiStopID mailxml_defs:ConsigneeMultiSt... mailxml_defs:ShipperStopNumb... mailxml_defs:ApptType mailxml_defs:PickupOrDelivery mailxml_defs:PalletPositionCount mailxml_defs:IncludesElectroni... <p>children</p> <ul style="list-style-type: none"> mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:DestinationEntry mailxml_tm:RecurringAppt mailxml_tm:OneTimeAppt mailxml_tm:SlotAvailability mailxml_tm:DetailInfo (0..∞) mailxml_tm:TrailerInfo mailxml_tm:ConsigneeFacility mailxml_tm:Comment
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:DestinationEntry mailxml_tm:RecurringAppt mailxml_tm:OneTimeAppt mailxml_tm:SlotAvailability mailxml_tm:DetailInfo mailxml_tm:TrailerInfo mailxml_tm:ConsigneeFacility mailxml_tm:Comment
annotation	documentation Query request for for availablity of a particular appointment.

element **DeliveryApptQueryResponse**

diagram	<p>DeliveryApptQueryResponse Response to the Query request for for availability of a particular appointment.</p> <p>attributes</p> <ul style="list-style-type: none"> grp mailxml_defs:RequestMs... mailxml_defs:ShipperApptRequ... mailxml_defs:ConsigneeApptID mailxml_defs:SchedulerID mailxml_defs:SchedulerCorplD mailxml_defs:SchedulerCRID mailxml_defs:ShipperMultiStopID mailxml_defs:ConsigneeMultiSt... mailxml_defs:ShipperStopNumb... mailxml_defs:ApptType mailxml_defs:PickupOrDelivery mailxml_defs:PalletPositionCount mailxml_defs:IncludesElectroni... <p>children</p> <ul style="list-style-type: none"> mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:QueryResults mailxml_tm:QueryError
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:QueryResults mailxml_tm:QueryError
annotation	documentation Response to the Query request for for availability of a particular appointment.

element **DeliveryApptShellCancelRequest**

diagram	<p>The diagram illustrates the structure of the DeliveryApptShellCancelRequest element. It is a complex type defined in the namespace <code>mailxml_tm:deliveryApptShellCancelRequestType</code>. The structure includes:</p> <ul style="list-style-type: none"> Attributes: A block containing several attributes from the <code>mailxml_defs</code> namespace: <ul style="list-style-type: none"> <code>ShipperApptRequ...</code> <code>ConsigneeApptID</code> <code>SchedulerID</code> <code>SchedulerCorpID</code> <code>SchedulerCRID</code> <code>ShipperMultiStopID</code> <code>ConsigneeMultiSt...</code> <code>ShipperStopNumb...</code> <code>ApptType</code> <code>PickupOrDelivery</code> <code>PalletPositionCount</code> <code>IncludesElectroni...</code> Children: A sequence of five elements: <ul style="list-style-type: none"> <code>mailxml_tm:SubmittingParty</code> <code>mailxml_tm:SubmittingSoftware</code> <code>mailxml_tm:SubmitterTrackingID</code> <code>mailxml_tm:DestinationEntry</code> <code>mailxml_tm:ReturnInfo</code> <p>DeliveryApptShellCancelRequest Request to cancel a delivery appointment shell to which content will be added later.</p>
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	mailxml_tm:deliveryApptShellCancelRequestType
children	<code>mailxml_tm:SubmittingParty</code> <code>mailxml_tm:SubmittingSoftware</code> <code>mailxml_tm:SubmitterTrackingID</code> <code>mailxml_tm:DestinationEntry</code> <code>mailxml_tm:ReturnInfo</code>
annotation	documentation Request to cancel a delivery appointment shell to which content will be added later.

element **DeliveryApptShellCancelResponse**

diagram	<p>The diagram illustrates the structure of the DeliveryApptShellCancelResponse element. It is a complex type defined in the namespace <code>mailxml_tm:deliveryApptShellCancelResponseType</code>. The structure includes:</p> <ul style="list-style-type: none"> Children: A sequence of three elements: <ul style="list-style-type: none"> <code>mailxml_tm:SubmitterTrackingID</code> <code>mailxml_tm:TrackingID</code> A choice between <code>mailxml_tm:DeliveryApptCancelAccept</code> and <code>mailxml_tm:DeliveryApptCancelReject</code>. <p>DeliveryApptShellCancelRespo... Response to a request to cancel a delivery appointment shell to which content will be added later.</p>
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	mailxml_tm:deliveryApptShellCancelResponseType
children	<code>mailxml_tm:SubmitterTrackingID</code> <code>mailxml_tm:TrackingID</code> <code>mailxml_tm:DeliveryApptCancelAccept</code> <code>mailxml_tm:DeliveryApptCancelReject</code>
annotation	documentation Response to a request to cancel a delivery appointment shell to which content will be added later.

element **DeliveryApptShellCreateRequest**

diagram	<p>DeliveryApptShellCreateRequest Request to create a delivery appointment shell to which content will be added later.</p>
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:ConsigneeFacility mailxml_tm:DestinationEntry mailxml_tm:MailClass mailxml_tm:RecurringAppt mailxml_tm:OneTimeAppt mailxml_tm:TrailerInfo mailxml_tm:Comment mailxml_tm:ValueAddedService
annotation	documentation Request to create a delivery appointment shell to which content will be added later.

element **DeliveryApptShellCreateResponse**

diagram	<p>DeliveryApptShellCreateRespo... Response to the request to create a delivery appointment shell to which content will be added later.</p>
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm

children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:DeliveryApptShellCreateAccept mailxml_tm:DeliveryApptShellCreateReject
annotation	documentation Response to the request to create a delivery appointment shell to which content will be added later.

element **DeliveryApptShellUpdateRequest**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:ConsigneeFacility mailxml_tm:DestinationEntry mailxml_tm:MailClass mailxml_tm:RecurringAppt mailxml_tm:OneTimeAppt mailxml_tm:TrailerInfo mailxml_tm:Comment mailxml_tm:ValueAddedService
annotation	documentation Request to update a delivery appointment shell to which content will be added later.

element **DeliveryApptShellUpdateResponse**

diagram	<p>Response to the request to update a delivery appointment shell to which content will be added later.</p>
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:DeliveryApptShellAccept mailxml_tm:DeliveryApptShellReject
annotation	documentation Response to the request to update a delivery appointment shell to which content will be added later.

element **DeliveryApptStatusQueryRequest**

diagram	<p>Query request for the status of a delivery appointment.</p>
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID
annotation	documentation Query request for the status of a delivery appointment.

element **DeliveryApptStatusQueryResponse**

diagram	<p>Response to the Query request for the status of a delivery appointment.</p> <p>Error issued when the query data cannot be provided.</p>
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:QueryResults mailxml_defs:QueryError
annotation	documentation Response to the Query request for the status of a delivery appointment.

element **DeliveryApptTransportationUpdateRequest**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	mailxml_tm:deliveryApptTransportationUpdateRequestType
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:TrailerInfo
annotation	documentation Request to update the transportation for a delivery appointment.

element **DeliveryApptTransportationUpdateResponse**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	mailxml_tm:deliveryApptTransportationUpdateResponseType
children	mailxml_tm:SubmitterTrackingID mailxml_tm:TrackingID mailxml_tm:DeliveryApptTransportationAccept mailxml_tm:DeliveryApptTransportationReject
annotation	documentation Response to the request to update the transportation for a delivery appointment.

element **DeliveryApptUpdate**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ApptBlockUpdate mailxml_tm:DetailInfo mailxml_tm:TrailerInfo mailxml_tm:ReturnInfo
used by	element DeliveryApptStatusQueryResponse/QueryResults

element **DeliveryApptUpdateRequest**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:DestinationEntry mailxml_tm:RecurringAppt mailxml_tm:OneTimeAppt mailxml_tm:DetailInfo mailxml_tm:TrailerInfo mailxml_tm:ConsigneeFacility mailxml_tm:Comment mailxml_tm:ETA mailxml_tm:ValueAddedService mailxml_tm:ReturnInfo
annotation	documentation Request to update a deliver appointment.

element **DeliveryApptUpdateResponse**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm

children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:DeliveryApptUpdateAccept mailxml_tm:DeliveryApptUpdateReject
annotation	documentation Response to the request to update a deliver appointment.

element **DeliveryContentCancelRequest**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	mailxml_tm:deliveryContentCancelRequestType
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:DestinationEntry mailxml_tm:ContentCancel
annotation	documentation Request to cancel delivery content.

element **DeliveryContentCancelResponse**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	mailxml_tm:deliveryContentCancelResponseType
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:DeliveryContentCancelAccept mailxml_tm:DeliveryContentCancelReject
annotation	documentation Response to the request to to cancel delivery content.

element **DeliveryContentCreateRequest**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:ConsigneeFacility mailxml_tm:DestinationEntry mailxml_tm:ContentDetailInfo
annotation	documentation Request from the Shipper to the Consignee to create content for delivery.

element **DeliveryContentCreateResponse**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:DeliveryContentAccept mailxml_tm:DeliveryContentReject
annotation	documentation Response to the request to create content for delivery.

element **DeliveryContentQueryRequest**

diagram	<p>The diagram shows the structure of the DeliveryContentQueryRequest element. It is a container for several attributes and a group of elements. The attributes include mailxml_tm:ConsigneeApptID, mailxml_tm:SchedulerID, mailxml_tm:SchedulerCorpID, mailxml_tm:SchedulerCRID, mailxml_tm:SchedulerContentID, mailxml_tm:ConsigneeContentID, mailxml_tm:RetrieveContentUp..., and mailxml_tm:RetrieveContentUp.... The group mailxml_tm:DeliveryConte... contains the following elements: mailxml_tm:SubmittingParty, mailxml_tm:SubmittingSoftware, mailxml_tm:SubmitterTrackingID, mailxml_tm:ConsigneeFacility, and mailxml_tm:DestinationEntry.</p>
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:ConsigneeFacility mailxml_tm:DestinationEntry
annotation	documentation Query request for delivery content.

element **DeliveryContentQueryResponse**

diagram	<p>The diagram shows the structure of the DeliveryContentQueryResponse element. It is a container for several attributes and a group of elements. The attributes include mailxml_tm:TrackingID, mailxml_tm:SubmitterTrackingID, mailxml_tm:QueryResults, and mailxml_tm:QueryError. The group mailxml_tm:DeliveryConte... contains the following elements: mailxml_tm:ConsigneeApptID, mailxml_tm:SchedulerID, mailxml_tm:SchedulerCorpID, mailxml_tm:SchedulerCRID, mailxml_tm:SchedulerContentID, mailxml_tm:ConsigneeContentID, mailxml_tm:RetrieveContentUp..., and mailxml_tm:RetrieveContentUp....</p>
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:QueryResults mailxml_tm:QueryError
annotation	documentation

	Response to the Query request for delivery content.
--	---

element **DeliveryContentUpdateRequest**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:ConsigneeFacility mailxml_tm:DestinationEntry mailxml_tm:ContentDetailInfoUpdate
annotation	documentation Request from the Shipper to the Consignee to update the content for delivery.

element **DeliveryContentUpdateResponse**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:DeliveryContentUpdateAccept mailxml_tm:DeliveryContentUpdateReject
annotation	documentation Response to the request from the Shipper to the Consignee to update the content for delivery.

element **DeliveryReApptRequest**

diagram	<p>DeliveryReApptRequest</p> <p>Request is sent from the Shipper to the Consignee if an appointment is cancelled and the Shipper wants to rebook the delivery using the same Consignee Appointment ID</p> <p>Attributes:</p> <ul style="list-style-type: none"> mailxml_defs:ResponseM... mailxml_defs:ShipperApptRequ... mailxml_defs:ConsigneeApptID mailxml_defs:SchedulerID mailxml_defs:SchedulerCorplD mailxml_defs:SchedulerCRID mailxml_defs:ShipperMultiStopID mailxml_defs:ConsigneeMultiSt... mailxml_defs:ShipperStopNumb... mailxml_defs:ApptType mailxml_defs:PickupOrDelivery mailxml_defs:PalletPositionCount mailxml_defs:IncludesElectroni... <p>Child Elements:</p> <ul style="list-style-type: none"> mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:ApptBlock mailxml_tm:DetailInfo mailxml_tm:TrailerInfo mailxml_tm:ValueAddedService <p>Cardinality: 1..∞</p>
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:ApptBlock mailxml_tm:DetailInfo mailxml_tm:TrailerInfo mailxml_tm:ValueAddedService
annotation	<p>documentation</p> <p>Request is sent from the Shipper to the Consignee if an appointment is cancelled and the Shipper wants to rebook the delivery using the same Consignee Appointment ID</p>

element DispatchContainerInfoNotification

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:TransportationSummaryBlock mailxml_tm:TransportationGeoDataBlock mailxml_tm:TransportationContainerStatusBlock
annotation	documentation Transportation mesaging

element DispatchContainerInfoResponse

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:DispatchContainerInfoAccept mailxml_tm:DispatchContainerInfoReject
annotation	documentation Response to the notification for dispatch container information.

element GoodsReceiptResponse

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:OK mailxml_tm:ReturnInfo
annotation	documentation Response to the consignee goods response message.

element **OpenApptQueryRequest**

diagram	<p>The diagram shows the structure of the OpenApptQueryRequest element. It is a container element with a description: "Query request for available delivery appointments." It contains a group of attributes: mailxml_defs:QueryMsgH..., mailxml_defs:SchedulerID, mailxml_defs:SchedulerCorpID, and mailxml_defs:ApptType. It also contains a sequence of child elements: mailxml_tm:SubmittingParty, mailxml_tm:SubmittingSoftware, mailxml_tm:SubmitterTrackingID (indicated as optional with a dashed border), mailxml_tm:ConsigneeFacility, and mailxml_tm:OptionalAppt (indicated as optional with a dashed border). The sequence is marked with a cardinality of 1..∞.</p>
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:ConsigneeFacility mailxml_tm:OptionalAppt
annotation	documentation Query request for available delivery appointments.

element **OpenApptQueryResponse**

diagram	<p>The diagram shows the structure of the OpenApptQueryResponse element. It is a container element with a description: "Response to the query request for available delivery appointments." It contains a group of attributes: mailxml_defs:QueryMsgH..., mailxml_defs:SchedulerID, mailxml_defs:SchedulerCorpID, and mailxml_defs:ApptType. It also contains a sequence of child elements: mailxml_tm:TrackingID (indicated as optional with a dashed border), mailxml_tm:SubmitterTrackingID (indicated as optional with a dashed border), mailxml_tm:QueryResults, and mailxml_defs:QueryError (indicated as optional with a dashed border). The sequence is marked with a cardinality of 1..∞. A note below the mailxml_defs:QueryError element states: "Error issued when the query data cannot be provided."</p>
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:QueryResults mailxml_defs:QueryError
annotation	documentation Response to the query request for available delivery appointments.

element **PartnerApptQueryRequest**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:ConsigneeFacility
annotation	<p>documentation</p> <p>Request from a company such as a printer or logistics company to query appointments on behalf of their business partner such as the mail owner.</p>

element **PartnerApptQueryResponse**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:QueryResults mailxml_tm:QueryError
annotation	<p>documentation</p> <p>Response to the request from a company such as a printer or logistics company to query appointments on behalf of their business partner such as the mail owner.</p>

element **PartnerContentAssignmentRequest**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID

	mailxml_tm:CurrentPartnerOwner mailxml_tm:PartnerContentAssignedTo
annotation	documentation Request from a users such as owner, preparer, consolidator, scheduler to assign the content to another user

element **PartnerContentAssignmentResponse**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:PartnerContentAssignmentAccepted mailxml_tm:PartnerContentAssignmentRejected
annotation	documentation Response to the request from a user for assignment of content to other user

element **PickupApptCancelRequest**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:ReturnInfo
annotation	documentation Request to cancel a pickup delivery appointment.

element **PickupApptCancelResponse**

diagram	
---------	--

namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:DeliveryApptCancelAccept mailxml_tm:DeliveryApptCancelReject
annotation	documentation Response to a request to cancel a pickup delivery appointment.

element **PickupApptCreateRequest**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:ApptBlock mailxml_tm:DetailInfo
annotation	documentation Request to create a pickup delivery appointment.

element **PickupApptCreateResponse**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:PickupApptCreateAccept mailxml_tm:PickupApptCreateReject
annotation	documentation Response to a request to create a pickup delivery appointment.

element PickupApptUpdateRequest

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:ApptBlock mailxml_tm:DetailInfo
annotation	documentation Request to update a pickup delivery appointment.

element PickupApptUpdateResponse

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:PickupApptUpdateAccept mailxml_tm:PickupApptUpdateReject
annotation	documentation Response to a request to update a pickup delivery appointment.

element **RecurringApptQueryRequest**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:ConsigneeFacility
annotation	documentation Query request for recurring appointment information.

element **RecurringApptQueryResponse**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:QueryResults mailxml_tm:QueryError
annotation	documentation Response to the query for recurring appointment information.

element **ScheduledAppt**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	xs:dateTime
used by	complexType apptBlockGoodsType apptInfoType

element **StaleContentDelivery**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_defs:DataRecipient mailxml_tm:PushMessageID mailxml_tm:DeliverySummary
annotation	documentation Push from USPS to Customer with the Stale Content Data.

element **StaleContentNotification**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm

children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:PushMessageID mailxml_tm:NotificationDate mailxml_tm:StaleContentNotificationElement
annotation	documentation Notification from USPS to customer informing that stale conten exist which will be deleted in 90 days.

element **StaleContentQueryRequest**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:ConsigneeFacility mailxml_tm:DestinationEntry mailxml_tm:NumberOfDaysStale mailxml_tm:RequestContentIDOnly
annotation	documentation Query request for stale delivery content.

element **StaleContentQueryResponse**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:QueryResults mailxml_tm:QueryError
annotation	documentation Response to the Query request for stale delivery content.

element **UnscheduledConsigneeGoodsReceipt**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ApptBlockUnsched... mailxml_tm:DetailInfo mailxml_tm:TrailerInfo mailxml_tm:ReturnInfo
annotation	documentation A report or message indicating delivery closeout status for an unscheduled delivery.

namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ApptBlockUnscheduledGoodsReceipt mailxml_tm:DetailInfo mailxml_tm:TrailerInfo mailxml_tm:ReturnInfo
used by	element AllApptCloseoutResponse/AllDeliveryApptCloseoutAccept complexType allDeliveryApptCloseoutAcceptType
annotation	documentation A report or message indicating delivery closeout status for an unscheduled delivery.

element **UnscheduledConsigneeGoodsReceiptDelivery**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_defs:DataRecipient mailxml_tm:UserLicenseCode mailxml_tm:MaidatJobID mailxml_tm:CustomerGroupID mailxml_tm:MailingGroupID mailxml_tm:PushMessageID mailxml_tm:ApptBlockUnscheduledGoodsReceipt mailxml_tm:DetailInfo mailxml_tm:TrailerInfo
annotation	documentation Delivery by the USPS of an unscheduled consignee goods receipt.

element **UnscheduledConsigneeGoodsReceiptNotification**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:CRID mailxml_tm:PushMessageID mailxml_tm:UserLicenseCode mailxml_tm:MaidatJobID mailxml_tm:CustomerGroupID mailxml_tm:MailingGroupID mailxml_tm:NotificationDate

annotation	documentation Notification by USPS that an unscheduled consignee goods receipt is ready for pickup.
------------	--

element **USPSDeliveryContentUpdatedDelivery**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_defs:DataRecipient mailxml_tm:PushMessageID mailxml_tm:DeliveryContentUpdated
annotation	documentation Delivery of content update information by USPS.

element **USPSDeliveryContentUpdatedNotification**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_defs:DataRecipient mailxml_tm:PushMessageID mailxml_tm:NotificationDate mailxml_tm:NotificationSummary
annotation	documentation Notification from USPS to Mailer/Preparer/Consolidator that mailing content has been changed.

element USPSDeliveryContentUpdatedQueryRequest

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:DestinationEntry mailxml_tm:USPSDeliveryContentUpdatedQueryParameters
annotation	documentation Query request for updated content from USPS

element USPSDeliveryContentUpdatedQueryResponse

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:QueryResults mailxml_defs:QueryError

annotation	documentation Response to the query for updated content from USPS
------------	--

complexType actualBedloadType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ActualBedloadPercent mailxml_tm:ActualBedloadCount
used by	elements apptBlockGoodsType/ActualBedload apptBlockUnscheduledGoodsType/ActualBedload

complexType actualPalletType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ActualPalletCount
used by	elements apptBlockGoodsType/ActualPalletCount apptBlockUnscheduledGoodsType/ActualPalletCount

complexType allDeliveryApptCloseoutAcceptType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ConsigneeGoodsReceipt mailxml_tm:UnscheduledConsigneeGoodsReceipt
used by	element AllApptCloseoutDelivery/FullServiceAllApptCloseoutAccept
annotation	documentation Response indicating that all delivery appointments have been closed.

complexType AppointmentInfoType

diagram	<pre> xsd:complexType base="baseType" name="AppointmentInfoType"> <xsd:sequence> <xsd:element base="string" name="mailxml_tm:ConsigneeApptID"></xsd:element> <xsd:element base="string" name="mailxml_tm:AppointmentDate"></xsd:element> <xsd:element base="string" name="mailxml_tm:ApptType"></xsd:element> <xsd:element base="string" name="mailxml_tm:ConsigneeFacility"></xsd:element> <xsd:element base="string" name="mailxml_tm:SchedulerID"></xsd:element> <xsd:element base="string" name="mailxml_tm:SchedulerCRID"></xsd:element> </xsd:sequence> </pre>
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ConsigneeApptID mailxml_tm:AppointmentDate mailxml_tm:ApptType mailxml_tm:ConsigneeFacility mailxml_tm:SchedulerID mailxml_tm:SchedulerCRID

complexType **apptBlockGoodsType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:DestinationEntry mailxml_tm:MailClass mailxml_tm:ScheduledConsigneeFacility mailxml_tm:ActualConsigneeFacility mailxml_tm:ScheduledAppt mailxml_tm:ActualTruckArrival mailxml_tm:StartTheClockDate mailxml_tm:ActualStartUnload mailxml_tm:ActualEndUnload mailxml_tm:ApptStatus mailxml_tm:ContainerCount mailxml_tm:ContainerErrorDescription mailxml_tm:ContainerID mailxml_tm:ContainerType mailxml_tm:IMcb mailxml_tm:IMtb mailxml_tm:IMpb mailxml_tm:ApptMethod mailxml_tm:USPSDetail mailxml_tm:VerificationLocation mailxml_tm:TransportationMethod mailxml_tm:ActualTotalPalletCount mailxml_tm:ActualPalletCount mailxml_tm:EvsSamplingTime mailxml_tm:EFileSamplingTime mailxml_tm:Irregularities mailxml_tm:Resolution mailxml_tm:ActualBedload mailxml_tm:ExemptionCode mailxml_tm:ValueAddedService
used by	elements ConsigneeGoodsReceipt/ApptBlockGoodsReceipt ConsigneeGoodsReceiptDelivery/ApptBlockGoodsReceipt


complexType **apptBlockRequestType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ConsigneeFacility mailxml_tm:PreferredAppt mailxml_tm:OptionalAppt mailxml_tm:Comment
used by	elements DeliveryApptCancelCreateRequest/ApptBlock DeliveryReApptRequest/ApptBlock


complexType **apptBlockUnscheduledGoodsType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:MailClass mailxml_tm:ActualConsigneeFacility mailxml_tm:ActualTruckArrival mailxml_tm:StartTheClockDate mailxml_tm:ActualStartUnload mailxml_tm:ActualEndUnload mailxml_tm:ApptStatus mailxml_tm:Irregularities mailxml_tm:Resolution mailxml_tm:ActualBedload mailxml_tm:ActualTotalPalletCount mailxml_tm:ActualPalletCount mailxml_tm:ValueAddedService
used by	elements UnscheduledConsigneeGoodsReceipt/ApptBlockUnscheduledGoodsReceipt UnscheduledConsigneeGoodsReceiptDelivery/ApptBlockUnscheduledGoodsReceipt


complexType **apptBlockUpdateType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ConsigneeFacility mailxml_tm:PreferredAppt mailxml_tm:OptionalAppt mailxml_tm:ETA mailxml_tm:Comment
used by	element DeliveryApptUpdate/ApptBlockUpdate

complexType **apptCloseoutDetailType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:UserID mailxml_tm:ApptCloseOut mailxml_tm:ApptCloseoutEmployeeContactInfo
used by	element apptInfoType/ApptCloseOutDetail

complexType **apptCloseoutNotAvailableResponseType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ReturnCode mailxml_tm:ReturnDescription
used by	element ApptInductionCloseoutResponse/ApptInductionCloseoutReject

complexType **apptCloseoutResponseType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:ApptInfo mailxml_tm:ContainerInductionInfo
used by	element ApptInductionCloseoutResponse/ApptInductionCloseoutAccept


complexType **apptInfoType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ApptConsigneeID mailxml_tm:ApptState mailxml_tm:ScheduledAppt mailxml_tm:ActualTruckArrival mailxml_tm:ActualStartUnload mailxml_tm:ActualEndUnload mailxml_tm:ApptCloseOutDetail
used by	element apptCloseoutResponseType/ApptInfo


complexType **availableApptType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:Start mailxml_tm:End mailxml_tm:Units mailxml_tm:ReturnInfo
used by	element OpenApptQueryResponse/QueryResults/AvailableAppt


complexType availableHourType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
used by	element availableSlotType/AvailableHours


complexType availableSlotType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:MailClass mailxml_tm:Perishable mailxml_tm:AvailableHours
used by	element DeliveryApptQueryResponse/QueryResults/AvailableSlots

complexType bedloadHandlingUnitType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:PreSortLevel mailxml_tm:IMpb mailxml_tm:IMtb
used by	elements bedloadUnitType/Bundles bedloadUnitType/Parcels bedloadUnitType/Sacks

complexType bedloadUnitType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:USPSContainerInfo mailxml_tm:Sacks mailxml_tm:Trays mailxml_tm:Parcels mailxml_tm:Bundles

used by	elements	contentUspsSummaryType/Bedload contentUspsSummaryUpdateType/Bedload uspsSummaryType/Bedload
---------	----------	---

complexType carrierType

diagram		
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm	
children	mailxml_tm:CarrierName mailxml_tm:CarrierCRID mailxml_tm:CarrierAddress mailxml_tm:URL mailxml_tm:CommonContact	
used by	element	trailerInfoType/Carrier

complexType containerInductionInfoType

diagram		
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm	
children	mailxml_tm:ContainerType	
used by	element	apptCloseoutResponseType/ContainerInductionInfo

complexType contentCancelType

diagram		
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm	
children	mailxml_tm:ReturnInfo	
used by	elements	deliveryContentCancelRequestType/ContentCancel deliveryContentCancelResponseType/DeliveryContentCancelAccept/ContentCancel deliveryContentCancelResponseType/DeliveryContentCancelReject/ContentCancel deliveryContentUpdatedType/ContentCancelInfo

complexType contentDetailInfoType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:DestinationEntry mailxml_tm:ShipperContainerGroupingID mailxml_tm:ConsigneeContainerGroupingID mailxml_tm:ShipperGroupingIDDescription mailxml_tm:ScheduledInductionDate mailxml_tm:NumberOfDaysStale mailxml_tm:MaildatSummary mailxml_tm:ContentUSPSSummary
used by	elements DeliveryContentCreateRequest/ContentDetailInfo StateContentQueryResponse/QueryResults/ContentDetailInfo deliverySummaryType/ContentDetailInfo deliveryContentAcceptType/ContentDetailInfo

complexType contentDetailInfoUpdateType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ShipperContainerGroupingID mailxml_tm:ConsigneeContainerGroupingID mailxml_tm:ShipperGroupingIDDescription mailxml_tm:ScheduledInductionDate mailxml_tm:MaildatSummary mailxml_tm:ContentUSPSSummary
used by	elements DeliveryContentQueryResponse/QueryResults/ContentDetailInfoUpdate DeliveryContentUpdateRequest/ContentDetailInfoUpdate deliveryContentUpdateAcceptType/ContentDetailInfoUpdate deliveryContentUpdatedType/ContentDetailInfoUpdate PartnerApptBlockType/ContentDetailInfoUpdate

complexType contentUspsSummaryType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	<p>mailxml_tm:DestinationDiscountIndicator mailxml_tm:ZoneSkippingIndicator mailxml_tm:FullServiceIndicator mailxml_tm:eInductionIndicator mailxml_tm:Pallets mailxml_tm:Bedload mailxml_tm:Perishable mailxml_tm:MailClass mailxml_tm:RateType mailxml_tm:InHomeStart mailxml_tm:InHomeEnd mailxml_tm:ProcessingCategory mailxml_tm:PriorityMailIndicator mailxml_tm:VerificationLocation mailxml_tm:NewsIndicator mailxml_tm:EvsIndicator mailxml_tm:MailContentName mailxml_tm:MailPreparerID mailxml_tm:MailPreparerCRID mailxml_tm:AdvanceMailingID mailxml_tm:EFileNumber mailxml_tm:ContainsAutoMail</p>
used by	<p>element contentDetailInfoType/ContentUSPSSummary</p>

complexType contentUspsSummaryUpdateType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:DestinationDiscountIndicator mailxml_tm:ZoneSkippingIndicator mailxml_tm:FullServiceIndicator mailxml_tm:elInductionIndicator mailxml_tm:Pallets mailxml_tm:Bedload mailxml_tm:Perishable mailxml_tm:MailClass mailxml_tm:RateType mailxml_tm:InHomeStart mailxml_tm:InHomeEnd mailxml_tm:ProcessingCategory mailxml_tm:PriorityMailIndicator mailxml_tm:VerificationLocation mailxml_tm:NewsIndicator mailxml_tm:EvsIndicator mailxml_tm:MailContentName mailxml_tm:MailPreparerID mailxml_tm:MailPreparerCRID mailxml_tm:AdvanceMailingID mailxml_tm:EFileNumber mailxml_tm:ContainsAutoMail
used by	element contentDetailInfoUpdateType/ContentUSPSSummary

complexType csaDispatchType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:DispatchTime mailxml_tm:ArrivalTime mailxml_tm:DaysOfWeek mailxml_tm:TripNumber mailxml_tm:RecurringApptSeqID mailxml_tm:USPSPublicationID mailxml_tm:TripVolume mailxml_tm:ContainerDestinationZipCode mailxml_tm:FacilityLocaleKey mailxml_tm:MailClass mailxml_tm:PackageServicesSubClass mailxml_tm:ProcessingCategory mailxml_tm:ProcessingCode mailxml_tm:ProcessingCodeLabel mailxml_tm:MinimumLoadForContainer mailxml_tm:ContainerReadyTime mailxml_tm:SeparationNumber mailxml_tm:LabelTo mailxml_tm:LabelToZip mailxml_tm:CriticalAcceptanceTime
used by	element csaInfoType/CSADispatch

complexType csaInfoType

diagram	
---------	--

namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:CSADispatch mailxml_tm:ReturnInfo
used by	element CustomerSupplierAgreementQueryResponse/QueryResults/CSAInfo

complexType deliveryApptAcceptType


diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:DestinationEntry mailxml_tm:RecurringAppt mailxml_tm:OneTimeAppt mailxml_tm:DetailInfo mailxml_tm:TrailerInfo mailxml_tm:ConsigneeFacility mailxml_tm:Comment mailxml_tm:ReturnInfo
used by	elements DeliveryApptCancelCreateResponse/DeliveryApptAccept DeliveryApptCreateResponse/DeliveryApptCreateAccept

complexType deliveryApptContentRemoveAcceptType


diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ContentID

used by	element DeliveryApptContentRemoveResponse/DeliveryApptContentRemoveAccept
---------	--

complexType **deliveryApptContentRemoveRejectType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ContentID mailxml_tm:ReturnInfo
used by	element DeliveryApptContentRemoveResponse/DeliveryApptContentRemoveReject

complexType **deliveryApptRejectType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ReturnInfo
used by	elements DeliveryApptCreateResponse/DeliveryApptCreateReject DeliveryApptCancelCreateResponse/DeliveryApptReject

complexType **deliveryApptShellAcceptType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ConsigneeFacility mailxml_tm:RecurringAppt mailxml_tm:OneTimeAppt mailxml_tm:TrailerInfo mailxml_tm:DestinationEntry mailxml_tm:MailClass mailxml_tm:ReturnInfo
used by	elements DeliveryApptShellUpdateResponse/DeliveryApptShellAccept DeliveryApptShellCreateResponse/DeliveryApptShellCreateAccept

complexType deliveryApptShellCancelRequestType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:DestinationEntry mailxml_tm:ReturnInfo
used by	element DeliveryApptShellCancelRequest

complexType deliveryApptShellCancelResponseType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmitterTrackingID mailxml_tm:TrackingID mailxml_tm:DeliveryApptCancelAccept mailxml_tm:DeliveryApptCancelReject
used by	element DeliveryApptShellCancelResponse

complexType deliveryApptShellRejectType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:DestinationEntry mailxml_tm:ReturnInfo
used by	elements DeliveryApptShellCreateResponse/DeliveryApptShellCreateReject DeliveryApptShellUpdateResponse/DeliveryApptShellReject

complexType deliveryApptTransportationUpdateRequestType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:TrailerInfo
used by	element DeliveryApptTransportationUpdateRequest

complexType deliveryApptTransportationUpdateResponseType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmitterTrackingID mailxml_tm:TrackingID mailxml_tm:DeliveryApptTransportationAccept mailxml_tm:DeliveryApptTransportationReject
used by	element DeliveryApptTransportationUpdateResponse

complexType deliveryApptUpdateAcceptType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:DestinationEntry mailxml_tm:RecurringAppt mailxml_tm:OneTimeAppt mailxml_tm:DetailInfo mailxml_tm:TrailerInfo mailxml_tm:ConsigneeFacility mailxml_tm:Comment mailxml_tm:ReturnInfo
used by	element DeliveryApptUpdateResponse/DeliveryApptUpdateAccept

complexType deliveryApptUpdateRejectType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ReturnInfo
used by	element DeliveryApptUpdateResponse/DeliveryApptUpdateReject

complexType deliveryContentAcceptType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ConsigneeFacility mailxml_tm:DestinationEntry mailxml_tm:ContentDetailInfo mailxml_tm:ReturnInfo
used by	element DeliveryContentCreateResponse/DeliveryContentAccept

complexType deliveryContentCancelRequestType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:SubmitterTrackingID mailxml_tm:DestinationEntry mailxml_tm:ContentCancel
used by	element DeliveryContentCancelRequest

complexType deliveryContentCancelResponseType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrackingID mailxml_tm:SubmitterTrackingID mailxml_tm:DeliveryContentCancelAccept mailxml_tm:DeliveryContentCancelReject
used by	element DeliveryContentCancelResponse

complexType deliveryContentRejectType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm

children	mailxml_tm:DestinationEntry mailxml_tm:ReturnInfo
used by	element DeliveryContentCreateResponse/DeliveryContentReject

complexType **deliveryContentUpdateAcceptType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ConsigneeFacility mailxml_tm:DestinationEntry mailxml_tm:ContentDetailInfoUpdate mailxml_tm:ReturnInfo
used by	element DeliveryContentUpdateResponse/DeliveryContentUpdateAccept

complexType **deliveryContentUpdatedType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ConsigneeFacility mailxml_tm:DestinationEntry mailxml_tm:ContentDetailInfoUpdate mailxml_tm:ContentCancelled mailxml_tm:ContentCancelInfo mailxml_tm:ReturnInfo

used by	elements	USPSDeliveryContentUpdatedDelivery/DeliveryContentUpdated USPSDeliveryContentUpdatedQueryResponse/QueryResults/DeliveryContentUpdated
---------	----------	--

complexType deliveryContentUpdateRejectType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:DestinationEntry mailxml_tm:ReturnInfo
used by	element DeliveryContentUpdateResponse/DeliveryContentUpdateReject

complexType deliverySummaryType


diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ConsigneeFacility mailxml_tm:DestinationEntry mailxml_tm:ContentDetailInfo
used by	element StaleContentDelivery/DeliverySummary

complexType detailInfoType


diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ShipperContainerGroupingID mailxml_tm:ConsigneeContainerGroupingID mailxml_tm:StartTheClockDate mailxml_tm:ShipperGroupingIDDescription mailxml_tm:MaidatSummary mailxml_tm:USPSSummary mailxml_tm:ConsigneeContentID

used by	elements	ConsigneeGoodsReceipt/DetailInfo ConsigneeGoodsReceiptDelivery/DetailInfo DeliveryApptCancelCreateRequest/DetailInfo DeliveryApptCreateRequest/DetailInfo DeliveryApptQueryRequest/DetailInfo DeliveryApptQueryResponse/QueryResults/DetailInfo DeliveryApptUpdate/DetailInfo DeliveryApptUpdateRequest/DetailInfo DeliveryReApptRequest/DetailInfo PickupApptCreateRequest/DetailInfo PickupApptCreateResponse/PickupApptCreateAccept/DetailInfo PickupApptCreateResponse/PickupApptCreateReject/DetailInfo PickupApptUpdateRequest/DetailInfo PickupApptUpdateResponse/PickupApptUpdateAccept/DetailInfo PickupApptUpdateResponse/PickupApptUpdateReject/DetailInfo UnscheduledConsigneeGoodsReceipt/DetailInfo UnscheduledConsigneeGoodsReceiptDelivery/DetailInfo deliveryApptAcceptType/DetailInfo deliveryApptUpdateAcceptType/DetailInfo
---------	----------	--


complexType eFileSamplingTimeType

diagram		
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm	
children	mailxml_tm:EFileNumber mailxml_tm:EFileSamplingTime	
used by	element	apptBlockGoodsType/EFileSamplingTime

complexType maildatSummaryType


diagram		
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm	
children	mailxml_tm:UserLicenseCode mailxml_tm:MaildatJobID mailxml_tm:DatabaseContainerID mailxml_tm:IMcb mailxml_tm:VerificationZip4 mailxml_tm:IMpb mailxml_tm:IMtb	
used by	elements	contentDetailInfoType/MaildatSummary contentDetailInfoUpdateType/MaildatSummary detailInfoType/MaildatSummary

complexType oneTimeApptType


diagram		
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm	

children	mailxml_tm:PreferredAppt mailxml_tm:OptionalAppt
used by	elements DeliveryApptCreateRequest/OneTimeAppt DeliveryApptQueryRequest/OneTimeAppt DeliveryApptQueryResponse/QueryResults/OneTimeAppt DeliveryApptUpdateRequest/OneTimeAppt DeliveryApptShellCreateRequest/OneTimeAppt DeliveryApptShellUpdateRequest/OneTimeAppt deliveryApptAcceptType/OneTimeAppt deliveryApptUpdateAcceptType/OneTimeAppt deliveryApptShellAcceptType/OneTimeAppt


complexType optionalApptType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:Start mailxml_tm:End
used by	elements OpenApptQueryRequest/OptionalAppt apptBlockRequestType/OptionalAppt oneTimeApptType/OptionalAppt pickupApptBlockRequestType/OptionalAppt

complexType optReturnInfoType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ConsigneeFacility mailxml_tm:ReturnCode mailxml_tm:ReturnDescription
used by	elements DeliveryApptCancelRequest/ReturnInfo contentCancelType/ReturnInfo deliveryApptShellCancelRequestType/ReturnInfo

complexType palletPresortType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:USPSContainerInfo
used by	element palletUnitType/PalletPreSortLevel

complexType palletUnitType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:PalletPreSortLevel mailxml_tm:USPSContainerInfo
used by	elements contentUspsSummaryType/Pallets contentUspsSummaryUpdateType/Pallets uspsSummaryType/Pallets

complexType PartnerApptBlockType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ConsigneeFacility mailxml_tm:ConsigneeApptID mailxml_tm:ScheduledAppt mailxml_tm:Comment mailxml_tm:MailClass mailxml_tm:TrailerInfo mailxml_tm:ContentDetailInfoUpdate
used by	element PartnerApptQueryResponse/QueryResults/ApptBlock

complexType partnerContentAssignmentType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:PartnerIdentifier mailxml_tm:ConsigneeContentID mailxml_tm:DestinationEntry
used by	elements PartnerContentAssignmentRequest/PartnerContentAssignedTo PartnerContentAssignmentResponse/PartnerContentAssignmentAccepted
annotation	documentation Type to define the combination of ConsigneeContentIDs and assigned users

complexType pickupApptBlockRequestType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:SubmittingParty mailxml_tm:SubmittingSoftware mailxml_tm:ConsigneeFacility mailxml_tm:PickupLocation mailxml_tm:PreferredAppt mailxml_tm:OptionalAppt mailxml_tm:Comment mailxml_tm:TransportationResponsibility
used by	elements PickupApptCreateRequest/ApptBlock PickupApptUpdateRequest/ApptBlock PickupApptCreateResponse/PickupApptCreateReject/ApptInfo PickupApptUpdateResponse/PickupApptUpdateReject/ApptInfo

complexType presortType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
used by	elements bedloadHandlingUnitType/PreSortLevel trayHandlingUnitType/PreSortLevel

complexType recurringApptBlockType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ConsigneeFacility mailxml_tm:RecurringData mailxml_tm:RecurringApptStatus mailxml_tm:USPSSummary mailxml_tm:PostalClass mailxml_tm:ReturnInfo
used by	element RecurringApptQueryResponse/QueryResults/RecurringApptBlock

complexType recurringApptType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:EffectiveStartDate mailxml_tm:EffectiveEndDate mailxml_tm:ApptTime mailxml_tm:DayFrequency mailxml_tm:WeekFrequency
used by	elements DeliveryApptCreateRequest/RecurringAppt DeliveryApptQueryRequest/RecurringAppt DeliveryApptQueryResponse/QueryResults/RecurringAppt DeliveryApptUpdateRequest/RecurringAppt DeliveryApptShellCreateRequest/RecurringAppt DeliveryApptShellUpdateRequest/RecurringAppt deliveryApptAcceptType/RecurringAppt deliveryApptUpdateAcceptType/RecurringAppt deliveryApptShellAcceptType/RecurringAppt recurringApptBlockType/RecurringData

complexType slotAvailabilityType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ApptType mailxml_tm:MailClass mailxml_tm:Perishable mailxml_tm:ApptStartTime mailxml_tm:ApptEndTime mailxml_tm:ApplyTiers
used by	elements DeliveryApptQueryRequest/SlotAvailability DeliveryApptQueryResponse/QueryResults/SlotAvailability


complexType staleContentNotificationElementType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ConsigneeFacility mailxml_tm:ConsigneeContentID mailxml_tm:NumberOfDaysStale mailxml_tm:DestinationEntry
used by	element StaleContentNotification/StaleContentNotificationElement


complexType trailerInfoType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:Trailer mailxml_tm:Carrier mailxml_tm:BillOfLadingNumber
used by	elements deliveryApptTransportationUpdateResponseType/DeliveryApptTransportationAccept ConsigneeGoodsReceipt/TrailerInfo ConsigneeGoodsReceiptDelivery/TrailerInfo DeliveryApptCancelCreateRequest/TrailerInfo DeliveryApptCreateRequest/TrailerInfo DeliveryApptQueryRequest/TrailerInfo DeliveryApptQueryResponse/QueryResults/TrailerInfo DeliveryApptUpdate/TrailerInfo DeliveryApptUpdateRequest/TrailerInfo DeliveryApptShellCreateRequest/TrailerInfo DeliveryApptShellUpdateRequest/TrailerInfo DeliveryReApptRequest/TrailerInfo UnscheduledConsigneeGoodsReceipt/TrailerInfo UnscheduledConsigneeGoodsReceiptDelivery/TrailerInfo deliveryApptAcceptType/TrailerInfo deliveryApptTransportationUpdateRequestType/TrailerInfo deliveryApptUpdateAcceptType/TrailerInfo deliveryApptShellAcceptType/TrailerInfo PartnerApptBlockType/TrailerInfo


complexType trailerType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TrailerNumber mailxml_tm:TrailerLength
used by	element trailerInfoType/Trailer

complexType transportationContainerBlockType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TransportationID mailxml_tm:StopDesignator mailxml_tm:ContentsBarcode mailxml_tm:ContentsBarcodeType mailxml_tm:ContentsBarcodeStatus mailxml_tm:BarcodeConstructCode mailxml_tm:ThirdPartyJobID mailxml_tm:FASTContentID mailxml_tm:ActualShipperArrivalDateTime
used by	element transportationGeoDataBlockType/Containers

complexType transportationContainerStatusBlockType

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ContentsBarcode mailxml_tm:ScanDateTime mailxml_tm:Latitude mailxml_tm:Longitude mailxml_tm:LocationDescription mailxml_tm:City mailxml_tm:State mailxml_tm:ZIP mailxml_tm:ScanEvent mailxml_tm:UserOptionField mailxml_tm:AppointmentNumber
used by	element transportationGeoDataBlockType/Containers

namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:ContentsBarcode mailxml_tm:ScanDateTime mailxml_tm:Latitude mailxml_tm:Longitude mailxml_tm:LocationDescription mailxml_tm:City mailxml_tm:State mailxml_tm:ZIP mailxml_tm:ScanEvent mailxml_tm>UserOptionField mailxml_tm:AppointmentNumber mailxml_tm:AppointmentNumberIdentifier
used by	element DispatchContainerInfoNotification/TransportationContainerStatusBlock

complexType **transportationDetailBlockType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TransportationID mailxml_tm:StopDesignator mailxml_tm:AppointmentNumber mailxml_tm:AppointmentNumberIdentifier mailxml_tm:FASTSchedulerID mailxml_tm:EstimatedArrivalDateTime mailxml_tm:ActualShipperArrivalDateTime mailxml_tm:ActualReceiverArrivalDateTime mailxml_tm:StopStatus
used by	element transportationSummaryBlockType/Stops

complexType **transportationGeoDataBlockType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TransportationID mailxml_tm:LocationDateTime mailxml_tm:Latitude mailxml_tm:Longitude mailxml_tm:City mailxml_tm:State mailxml_tm:ZIP mailxml_tm:LocationStatus mailxml_tm:Containers
used by	element DispatchContainerInfoNotification/TransportationGeoDataBlock

complexType **transportationSummaryBlockType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:TransportationID mailxml_tm:LoadTruckDispatchNumber mailxml_tm:TargetShipDateTime mailxml_tm:Stops
used by	element DispatchContainerInfoNotification/TransportationSummaryBlock

complexType **trayHandlingUnitType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:PreSortLevel mailxml_tm:IMpb mailxml_tm:IMtb
used by	element bedloadUnitType/Trays

complexType **uspsClosedBySVType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:AutoScan mailxml_tm:ManualScan
used by	element uspsDetailType/USPSClosedBySV

complexType **uspsContainerInfoType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:MailOwnerCRID mailxml_tm:MailOwnerID mailxml_tm:USPSPublicationID mailxml_tm:ActualPieceCount mailxml_tm:ContainerWeight mailxml_tm:IMcb mailxml_tm:IMcbInfo mailxml_tm:SiblingBarcode mailxml_tm:PostInductionStatus mailxml_tm:ContainerDestination3digitZIP mailxml_tm:ContainerDestination5digitZIP
used by	elements bedloadUnitType/USPSContainerInfo palletUnitType/USPSContainerInfo palletPresortType/USPSContainerInfo

complexType **uspsDetailType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:USPSMultiApptID mailxml_tm:USPSClosedBySV
used by	element apptBlockGoodsType/USPSDetail

complexType **uspsSummaryType**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
children	mailxml_tm:DestinationDiscountIndicator mailxml_tm:ZoneSkippingIndicator mailxml_tm:FullServiceIndicator mailxml_tm:InductionIndicator mailxml_tm:Pallets mailxml_tm:Bedload mailxml_tm:Perishable mailxml_tm:MailClass mailxml_tm:RateType mailxml_tm:InHomeStart mailxml_tm:InHomeEnd mailxml_tm:ProcessingCategory mailxml_tm:NewsIndicator mailxml_tm:PriorityMailIndicator mailxml_tm:VerificationLocation mailxml_tm:EvIndicator mailxml_tm:MailContentName mailxml_tm:MailPreparerID mailxml_tm:MailPreparerCRID mailxml_tm:AdvanceMailingID mailxml_tm:EFileNumber mailxml_tm:ContainsAutoMail
used by	elements detailInfoType/USPSSummary recurringApptBlockType/USPSSummary

simpleType **appointmentNumberIdentifierType**

namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	restriction of xs:string
used by	elements transportationContainerStatusBlockType/AppointmentNumberIdentifier transportationDetailBlockType/AppointmentNumberIdentifier

simpleType **contentsBarcodeStatusType**

namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	restriction of xs:string
used by	element transportationContainerBlockType/ContentsBarcodeStatus

simpleType **contentsBarcodeType**

namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	restriction of xs:string
used by	element transportationContainerBlockType/ContentsBarcodeType

simpleType **csaStatusType**

namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	restriction of xs:string
used by	attribute csaInfoType/@CSAStatus

simpleType **csaTemplateType**

namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	restriction of xs:string
used by	attribute csaDispatchType/@CSATemplate

simpleType **IMcbInfoType**

namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	restriction of xs:string
used by	element uspsContainerInfoType/IMcbInfo

simpleType **locationStatusType**

namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	restriction of xs:string
used by	element transportationGeoDataBlockType/LocationStatus

simpleType **packageServicesType**

namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	restriction of xs:string

used by	element csaDispatchType/PackageServicesSubClass
---------	--

simpleType **processingCodeType**

namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	restriction of xs:string
used by	element csaDispatchType/ProcessingCode

simpleType **scanEventType**

namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	restriction of xs:string
used by	element transportationContainerStatusBlockType/ScanEvent

simpleType **stopStatusType**

namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	restriction of xs:string
used by	element transportationDetailBlockType/StopStatus

simpleType **valueAddedServiceType**

namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	restriction of xs:string
used by	elements DeliveryApptCreateRequest/ValueAddedService DeliveryApptUpdateRequest/ValueAddedService DeliveryApptShellCreateRequest/ValueAddedService DeliveryApptShellUpdateRequest/ValueAddedService DeliveryReApptRequest/ValueAddedService apptBlockGoodsType/ValueAddedService apptBlockUnscheduledGoodsType/ValueAddedService

simpleType **verificationLocationType**

namespace	http://delivery-tech.org/Specs/mailxml26.0/mailxml_tm
type	restriction of xs:string
used by	elements apptBlockGoodsType/VerificationLocation contentUspsSummaryType/VerificationLocation contentUspsSummaryUpdateType/VerificationLocation uspsSummaryType/VerificationLocation